



Y.LIN ELECTRONICS CO.,LTD.

Data Sheet

Customer: _____
Part No: YLS0402/G/21/05-C
Sample No: YL20180321-923Y
Description: 0402 Green SMD
Item No: _____

Customer			
Check	Inspection	Approval	Date

Y.LIN			
Drawn	Check	Approval	Date
			2017/8/8

Mainland address:Jinhe The Third IndustrialZone,Zhangmutou Town,Dongguan,Guangdong,China

H.K address:Unit 503 5/F,Silvercord Tower 230 Canton Road Tsimshatsui

TEL:0769-87181888 FAX:0769-87187333 E-mail:yonglin@y-lin.com [Http://www.yong-lin.net](http://www.yong-lin.net)



Features:


- . Reflow Solderable
- . High Luminous Intensity and Low Power Dissipation
- . Good Reliability and Long Life
- . Complied With RoHS Directive

Technical Data Sheet

This product is generally used as indicator and luminary for electronic equipment such as household appliance, communication equipment, and dashboard.

Applications

- Optical indicator
- Indoor display
- Backlighting in dashboard and switch
- Flat backlighting for LCD, symbol and display
- General use



Notes:

- 1 . All dimension units are millimeters.
2. All dimension tolerance is $\pm 0.2\text{mm}$ unless otherwise noted.



Selection Guide

Part No.	Dice	Lens Type	Luminous intensity(mcd) @ 5mA			Viewing Angle
			Min	Typ	Max	201/2
YLS0402/G/21/05-C	Green (InGaN)	Water Clear	170	--	360	120

Note:

- 1.201/2 is the angle from optical centerline where the luminous intensity is 201/2 the optical centerline value.
- 2.The above luminous intensity measurement allowance tolerance $\pm 10\%$

Electrical / Optical Characteristics at Ta=25 °C

Parameter	Symbol	Min.	Typ.	Max	Units	test conditions
Forward Voltage	VF	2.7	--	3.1	V	IF=5mA
Reverse Current	IR	--	--	10	uA	VR = 5V
Dominate Wavelength	λ_d	525	530	535	nm	IF=5mA

Absolute Maximum Ratings at Ta=25 °C

Parameter	Symbol	Rating	Units
Power Dissipation	Pd	160	mW
DC Forward Current	IF	30	mA
Peak Forward Current [1]	IFP	100	mA
Reverse Voltage	VR	5	V
Electrostatic Discharge (HBM)	ESD	2000	V
Operating Temperature	Topr	-30~+85	°C
Storage Temperature	Tstg	-40~+100	°C

Note:

1. 1/10 Dut cycle,0.1ms pulse width.
2. The above forward voltage measure ment allowance tolerance $\pm 0.1V$.



BIN Range

Luminous Intensity (IV)				
BIN CODE	MIN	MAX	Unit	IF
R	170	220	mcd	5mA
S	220	280		
T	280	360		


Forward Voltange (VF)				
BIN CODE	MIN	MAX	Unit	IF
7	2.6	2.7	V	5mA
8	2.7	2.8		
9	2.8	2.9		
10	2.9	3.0		
11	3.0	3.1		

Dominant Wavelength (Hue)				
BIN CODE	MIN	MAX	Unit	IF
GB	525	530	nm	5mA
GC	530	535		




Typical optical characteristics curves


Ambient Temperature VS. Forward Current




Ambient Temperature (°C)




Forward Voltage VF(V)




Forward Current(mA)



Ambient Temperature TA(°C)



Wavelength λ (nm)



Emitted Angle120°



Reliability Test Items And Conditions

The reliability of products shall be satisfied with items listed below.

Confidence level :90%

LTPD :10%


Test Items	Test conditions	Quantity	Judging Criteria
Solderability	Solder Temperature: 240°C Solder Duration: (3.5±0.5) sec.	22	Solderable Area Over 95%
Thermal Shock Followed by High Temperature And High Humidity Cyclic	-40°→10min 5 Cycles ↑ ↓ shift(2~3)min 100°C →10 min. 25°C~55°C (90%~95%) RH 2 Cycles for 48 hrs., Recover for 2 hrs	22	C=0 & I**
Resistance For Soldering Heat	Reflow Soldering	22	C=0 & I**
DC Operating Life	1000 hrs. Forward Current: 30mA	22	C=0 & I**
High Temperature Storage	100°C → 1000 hrs	22	C=0 & I**
High Temperature And High Humidity Cyclic	25°C~55°C (90%~95%) RH 6 Cycles for 144 hrs., Recover for 2 hrs.	22	C=0 & I**

The technical information shown in the data sheets are limited to the typical characteristics and circuit examples of the referenced products.It does not constitute the warranting of industrial property nor the granting of any license.



SMT Reflow Soldering Instructions

- 1.Reflow soldering is not can do two times
- 2.When soldering , do not put stress on the LEDs during heating .




3.Product is highest resistant to 260°C, reflow but suggested the highest temperature of 270°C max.

Soldering iron

- 1.When hand soldering, the temperature of the iron must less than 300°C for 3 seconds
- 2.The hand solder should be done only one times

Repairing

Repair should not be done after the LEDs have been soldered. When repairing is unavoidable, a double-head soldering iron should be used (as below figure). It should be confirmed beforehand whether the characteristics of LEDs will or will not be damaged by repairing.



Storage

The package is sealed:


- 1.The LEDs Should be store at 5°C~30°C and 90% RH or less.
- 2.It is recommended that SMD out of their original packaging are used within one year.

The package is opened:

- 1.Completed within 168 hours.
- 2.Stored at 5°C~30°C and 60% RH or less.
- 3.LEDs stored more than 168 hours should be baked at about 60°C±5°C for at least 20 hours before solder assembly.

1.Do not stack together assembled PCBs containing LEDs. Impact may scratch the silicone lens or damage.


2.Not available in the situation of acidity for PH.





PACKAGING

包装方式:



Package: 3000 pcs/reel

Note: The tolerances unless mentioned is $\pm 0.1\text{mm}$, Unit: mm

Moisture Resistant Packaging

